



WTD021

Low Pressure Water Delivery Hose,
7 Bar

Code	ID (mm)	OD (mm)	Wall (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)	Max. Length (m)
WTD021-19x4	19	27	4	7	21	144	0,42	40
WTD021-25x4	25	33	4	7	21	192	0,53	40
WTD021-38x4.5	38	47	4,5	7	21	278	0,81	40
WTD021-51x5	51	61	5	7	21	390	1,30	40
WTD021-76x6	76	88	6	7	21	567	2,12	40
WTD021-102x6	102	114	6	7	21	772	2,95	40
WTD021-127x7	127	141	7	7	21	983	3,88	40
WTD021-152x7.5	152	167	7,5	7	21	1185	5,45	40
WTD021-203x8	203	219	8	7	21	1360	7,29	30.5
WTD021-254x8	254	270	8	7	21	1769	8,90	20
WTD021-305x9	305	323	9	7	21	2240	11,35	10

Application

Low pressure water hose for applications in irrigation and water discharge purposes

Temperature

-30°C to +85°C

Features

Kink resistant, easy handling and storage

Type

Mandrel built

Tube

Synthetic rubber, black, smooth, resistant to waste water up to 10ph

Reinforcement

High tensile textile cord fabric

Cover

Synthetic rubber, black, smooth with cloth impression, weather, ozone and abrasion resistant

Marking

Embossed or Transfer Label

Standards/Approvals

Comments